



Performance

Magnetic performance 4,000 Gauss
Patented Micromag style core

Volume 0.13 gal (500 ml)

Pressure 43 psi (3 Bar) operating pressure

Flow rate 14 gpm (3 m³/h)

Collection Capacity 0.9 lbs (400 g)

Temperature 212°F (100°C)

Construction

Magnet material Rare Earth Neodymium Iron Boron

Mesh filter 0.5mm, quick release mesh (for cleaning)

Valves 1" NPT (1.25" NPT adaptors included in kit)

Includes Additional Automatic Air Vent that has been packaged along with unit separately. The auto-vent will automatically release the trapped air maintaining heating efficiency

Warranty Industry leading 3 years

Its all in the box....

All you need to fit and service BoilerMag is contained in a simple retail friendly off-the-shelf package.

- BoilerMag filter unit
- 2 x 1" NPT valves
- 2 x 1.25" NPT adaptors
- Automatic air vent
- Spare o-rings
- Bowl spanner/cleaning tool
- Product guide
- Drain valve spanner
- Boiler sticker
- Pipe cut template

For larger applications, try our commercial and industrial ranges:



BoilerMag XL
(filter to suit 1½" pipe)



BoilerMag XT
(filter to suit 2"-12" pipes)

Eclipse Tools North America Inc
442 Millen Road Unit #9, Stoney Creek, Ontario, L8E 6H2
T 1-800-260-2124 F 1-800-260-1410
sales@eclipsetoolsinc.com www.boilermag.com



The Ultimate Filtration Solution

- Fast, easy install
- Dual flow technology™
- Premier performance
- Patented magnetic circuit
- Extracts both magnetic and non-magnetic debris



WITH AUTOMATIC AIR VENT FOR EXTRA CORROSION PROTECTION

BOILERMAG 3 YEAR WARRANTY

Celebrating 100 YEARS Manufacturing excellence

Installs in **minutes** protects for **years**

Combining high performance with ease of installation and servicing, BoilerMag uses tried and tested patented magnetic technology to remove virtually 100% of magnetite (sludge) and scale on the first pass through the filter.

Featuring “Dual Flow” technology it is the perfect choice for residential installations.


- Any direction install (pipework or filter)
- High volume collection capacity
- High performance dirt removal
- Includes Automatic Air Vent
- Easy “in-line” installation
- Available in 1” and 1¼”
- No block feature



Getting to Know Your BoilerMag


BoilerMag is designed for performance and practicality. The illustration below highlights the key features for installers, service contractors and property holders.

- 1 Simple flush access point - flush attachment available separately
- 2 Air vent/chemical dosing point
- 3 360° Adjustment - allows installation at any angle either pipework or filter



- 4 Requires minimal access space - unit does not have to be fully removed from pipework
- 5 High quality isolation valves included
- 6 Easy “In-Line” installation
- 7 No block mesh guard - removes scale and other non-magnetic debris

- 8 Patented magnetic circuit - ensures system cannot block
- 9 Patented magnetic core - large magnetic surface area



- 10 Dual flow technology - maximises dirt collection performance by ensuring that magnetite is exposed to the magnetic zone for longer

